

Model Number: C0801S1ULA-22420-XXXX

8-way Single L-band Active Dextra Series Combiner

With dual redundant amplifiers (OPT-R version) & -20 dB monitoring port



The **Dextra** combiner range has been designed for high resilience RF distribution, and optimum satellite signal quality. The combiners benefit from excellent RF performance and compact form factor as well as advanced functionality.

Advanced functionality:

- Dual redundant amplifiers (option)
- 20 dB monitor port on the front panel
- Web browser access (and SNMP) for control and monitoring
- Compact 1RU 19" chassis

Benefits & features:

- Highly resilient solution minimising the risk of expensive downtime for the satcoms user
- Dual redundant power supplies
- Dual redundant amplifiers (option)

Typical applications:

- Satellite operators, VSAT, teleports, and broadcasters
- High resilience RF distribution, and optimum satellite signal quality
- 850-2450 MHz to cover Ka-band and HTS applications

RF performance:

- Specified to ensure optimum signal quality with high throughput / high bandwidth satcoms.
- 850-2450 MHz operating range
- Excellent Gain flatness (frequency response)
- High return loss
- High linearity
- Low noise figure

Options: Dextra combiners can be specified with single amplifier or hot/cold-standby dual-redundant amplifier options. Please specify OPT-R for redundant amplifier option. This is remote configurable. The range covers 4-way and 8-way combiners and splitters in both single and dual configurations. 16-way splitters and combiners are available as single units. All these are supplied in a 1RU case for space efficient rack mounting.

















Model Number: C0801S1ULA-22420-XXXX

8-way Single L-band Active Dextra Series Combiner

Technical specifications and operating parameters

RF Parameters						
Capacity		8-way Combiner				
Front panel monitor		50Ω SMA -20dB, 16dB return loss			oss	
Frequency		850-2450MHz				
Connector & impedances		50Ω BNC	50Ω SMA	50Ω N-type	75Ω F-type	75Ω BNC
Gain		0 ± 1.0 dB		Mean across band		
Gain	850-2450 MHz	±0.8 dB	±0.8 dB	±0.8 dB	±1.0 dB	±1.0 dB
Flatness	Any 36 MHz	±0.25 dB	±0.25 dB	±0.25 dB	±0.3 dB	±0.3 dB
Input return loss	Typical	21 dB	21 dB	21 dB	21 dB	21 dB
	Minimum	16 dB	16 dB	16 dB	16 dB	16 dB
Output return loss	Typical	20 dB	20 dB	20 dB	20 dB	20 dB
	Minimum	16 dB	16 dB	16 dB	16 dB	16 dB
Isolation	Typical	28 dB	28 dB	28 dB	28 dB	28 dB
850- 2250MHz	Minimum	24 dB	24 dB	24 dB	24 dB	24 dB
Isolation	Typical	28 dB	28 dB	28 dB	24 dB	24 dB
2250- 2450MHz	Minimum	24 dB	24 dB	24 dB	22 dB	22 dB
Group	850-2450 MHz	2 ns maximum				
Delay	Any 36 MHz	1 ns maximum				
Amplifier Redundancy (Option OPT-R)		Dual redundant amplifier. Selectable hot or cold standby, 1:1 redundancy with auto switch over based on amplifier current monitoring.				
Noise figure		24 dB Max				
Output 1dB GCP		+10 dBm Min				
OIP3		+20 dBm Min				
OIP2		+30 dBm Min				
In Band Spurious		<-80 dBm				

Power				
AC Power	85-264Vac 50-60Hz	Fused 2A		
AC Consumption	<20W	At steady state.		
Input RF Power	16dBm	Absolute maximum		
PSU	Dual redundant PSUs with dual IEC inlets.	Diode OR		
Hot-swap PSU	No			

System Control		
Monitoring & Remote Control	Redundant amplifiers and power supplies monitored via RJ45 port with 10baseT/100baseTX Ethernet offering web browser access, SNMP and ETL proprietary TCP protocol	
Alarms	Dry contact, 9-way D-type alarm port for PSU supply. Full status and alarms are also available via the Ethernet interface.	
Display	Front panel LEDs for PSU, and amplifier status.	

Physical		
Dimensions	1U high x 350mm deep x 19" wide	
Weight	3 Kg	
Colour	White 00-E-55 semi-gloss	

Environmental		
Operating temperature	0 to 50°C	
Location	Indoor use only	
Storage temperature	-20°C to +75°C	
Humidity	85% non-condensing	

Options

Please add the relevant suffix to the model number to indicate your required connectors:

BNC 50 Ω - B5B5

BNC 75 Ω - B7B7

F-type 75 Ω - F7F7

N-type 50 Ω - N5N5

SMA 50 Ω - S5S5

Please use suffix **OPT-R** to specify the option of dual redundant amplifiers

ETL SYSTEMS LIMITED Coldwell Radio Station Madley Hereford England HR2 9NE

TELEPHONE +44 (0)1981 259020

EMAIL info@etlsystems.com

FACSIMILE +44 (0)1981 259021

www.etlsystems.com







